

# Declaration of Performance

Nº 01 / 4A06-4E06 / 17

**UNIQUE IDENTIFICATION CODE OF THE PRODUCTION TYPE:** Clay roofing tiles and fittings

- Clay roof tiles with sidelock and headlock:
  - Roof tiles Lógica Lusa (red base), Lógica Lusa (full color coverage base), Lógica Lusa (straw base)
  - Roof tiles Lógica Marselha (red base), Lógica Marselha (full color coverage base), Lógica Marselha (straw base)
  - Roof tiles Lógica plana (red base), Lógica plana (full color coverage base), Lógica Plana (straw base)
  - Roof tiles Lógica Onda (red base), Lógica Onda (full color coverage base)
  - TelhaSol 12
  - TelhaSol 10
  - TelhaSol 10 Super
  - TelhaSol Piemontesa
  - Telha Marselha MG
  - Telha Lusa MG
- Coordinated clay fittings:
  - Half tile, double tile, ventilation tile, lanterne base tile, eaves tile, ventilation step tile, no ventilation step tile.
- Non coordinated clay fittings:
  - Ridge, 45º right ridge, 45º left ridge, 3 ridge junction – F, 3 ridge junction – M/F, 4 ridge junction, T-ridge junction, sloped 3 ridge junction, ridge end cap, wedge, right verge, left verge, universal verge, hip end, 45º right hip end, 45º left hip end, corner eaves tile, lower eaves tile, upper eaves tile, corner eaves tile, corner internal eaves tile, modular ridge, hip end, lanterne, angular end cap for universal verge, angular end cap for lateral verges.

**INTENDED USE:**

Roof coverings and external wall claddings.

**MANUFACTURER:**

CT – COBERT TELHAS, S.A.  
 EN 361-1, Km 10, Outeiro da Cabeça  
 2565-594 Outeiro da Cabeça (Torres Vedras) - PORTUGAL

**SYSTEM OF EVALUATION AND VERIFICATION OF PERFORMANCE CERTAINTY (AVCP):** SISTEMA Nº 4

**HARMONIZED STANDARD:** EN 1304:2013

**DECLARED PERFORMANCE**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION	
Flexural strength	Comply	EN 1304:2013	
External fire performance	Deemed to satisfy		
Reaction to fire	Classe A1		
Water impermeability	Category 1 Test Method 2		Comply
Dimensions/dimensional variation	Technical Form ± 2 %		Comply
Durability	Roof Tiles Lógica and fittings: Level 1 (≥ 150 cycles) Telhasol, Telha MG and fittings: Level 2 (≥ 90 cycles)		Comply
Release of regulated substances	NPD		

The performance of the product identified above is in conformity with the set of declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

This declaration of performance is available in [www.rooftilescobert.com](http://www.rooftilescobert.com), in accordance with Article 7(3) of regulation (UE) No 305/2011.

Signed for and on behalf of the manufacturer by:

Outeiro da Cabeça, 09 Outubro 2017



Ana Bernardes  
 Quality manager